



Rua Solidônio Leite, 1.127
Fone 11 2154-2951

Rosca BSF – Tolerância de parafusos em qualidade media

(Fina British Standard) 55°

Rosca	Passo	Diâmetro Primitivo		Diâmetro Externo	
		Min./ mm	Max./ mm	Min./ mm	Max./ mm
3/16	32	4,171	4,255	4,633	4,763
7/32	28	4,884	4,976	5,418	5,556
1/4	26	5,631	5,725	6,205	6,350
9/32	26	6,419	6,518	6,993	7,142
5/16	22	7,094	7,198	7,780	7,933
3/8	20	8,600	8,712	9,357	9,525
7/16	18	10,089	10,209	10,932	11,113
1/2	16	11,557	11,682	12,510	12,700
9/16	16	13,139	13,272	14,092	14,288
5/8	14	14,577	14,712	15,669	15,875
11/16	14	16,160	16,300	17,252	17,463
3/4	12	17,544	17,693	18,827	19,050
13/16	12	19,129	19,281	20,411	20,638
7/8	11	20,589	20,747	21,991	22,225
1	10	23,607	23,774	25,151	25,400
1 1/8	9	26,594	26,769	28,316	28,575
1 1/4	9	29,761	29,944	31,483	31,750
1 3/8	8	32,703	32,893	34,646	34,925
1 1/2	8	35,872	36,068	37,816	38,100
1 5/8	8	39,042	39,243	40,983	41,275
1 3/4	7	41,915	42,126	44,146	44,450
2	7	48,255	48,476	50,485	50,800
2 1/4	6	54,206	54,440	56,814	57,150
2 1/2	6	60,548	60,790	63,155	63,500
2 3/4	6	66,891	67,140	69,497	69,850
3	5	72,685	72,946	75,824	76,200